



Fiber Optic Distribution Box 16 ports FQX-16-12+PW16

Description

HBY Model No. FQX-16-12+PW16 , this distribution box can realize the functions of fiber fusion, distribution and scheduling in the FTTH system. This fiber box made of new PC+ABS material, and its shell is strong and durable. And IP65's protection rating allows it to be installed and used outdoors. Internally, this kind FDB can also be fitted with a variety of stents to install adapters , mini steel splitter or cassette splitter.



Product Specifications

Item	Fiber Optic Distribution Box 16 ports
Dimension (mm)	285*175*80MM
Material	PC+ABS
Weight (Kg)	1.215
No. of Cable Inlet/Outlet	4IN-16OUT
Diameter of Cable(mm)	IN: 7mm-16.5mm OUT: 2-12.5mm
Adaptor accommodating	Max.16 port of SC, FC, LC, E2K
Splitter	One for 1x16 splitter; Two for 2x8 splitter
Working Temperature	-30deg.C~80deg.C
Protection Grade	IP65



Ordering Information

FiberNex PN	Capacity (single core)	Adaptor type	Description
FQX-16-12+PW16	16 Port	SC	Fiber Optic Subscriber Distribution box 16 Port SC type
FQX-16-12+PW16	16 Port	FC	Fiber Optic Subscriber Distribution box 16 Port FC type
FQX-16-12+PW16	16 Port	LC	Fiber Optic Subscriber Distribution box 16 Port LC type
FQX-16-12+PW16	16 Port	E2K	Fiber Optic Subscriber Distribution box 16 Port E2K type

*Does not including adaptors, pigtailed and splitter. Additional configurations can be made if required

Packing Info

- Carton packing: 15sets/carton
- Carton size: 58*31*49cm
- Weight: 19.5kg/carton

- www.hbyweb.ru
- www.hbyweb.com.br
- E-mail: sales@hbyweb.com