



Fiber Optic Adapter



SC/UPC-SC/UPC-Singlemode-Simplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.



Specification

Parameter	SC Adapter		
	SM	MM	UPC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		

Fiber Optic Adapter



SC/APC-SC/APC-Singlemode-Simplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.


Specification

Parameter	SC Adapter		
	SM		MM
	UPC	APC	UPC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		

Fiber Optic Adapter



SC/UPC-SC/UPC-Multi mode-Simplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.


Specification

Parameter	SC Adapter		
	SM		MM
Insertion Loss	UPC ≤0.2dB	APC ≤0.2dB	UPC ≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		

Fiber Optic Adapter



SC/UPC-SC/UPC-Singlemode-Duplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.


Specification

Parameter	SC Adapter		
	SM		MM
	UPC	APC	UPC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		

Fiber Optic Adapter



SC/APC-SC/APC-Singlemode-Duplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.



Specification

Parameter	SC Adapter		
	SM		MM
	UPC	APC	UPC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		

Fiber Optic Adapter



SC/UPC-SC/UPC-Multi mode-Duplex



- Low insertion loss
- Good repeatability
- High stability
- Good interchangeability

Describe

Fiber optic adapter, also called coupler, is a small device designed to terminate or link the fiber optic cables or fiber optic connectors between two fiber optic lines. By linking two connectors precisely, fiber optic adapters allow the light sources to be transmitted at most and lower the loss as much as possible. At the same time, fiber optic adapters have the merits of low insertion loss, good interchangeability and reproducibility.

Specification

Parameter	SC Adapter		
	SM		MM
	UPC	APC	UPC
Insertion Loss	≤0.2dB	≤0.2dB	≤0.2dB
Alternation loss	≤0.2dB		
Repeatability	≤0.2dB		
Durability	The change of 1000 interpolation times is less than 0.2dB		
Working Temperature	- 40 ~ 85 °C		
Storage Temperature	- 40 ~ 85 °C		